

## NorTorque model 200, 1/2", Adjustable Ratchet (Dual Scale)



The NorTorque<sup>®</sup> utilises Norbar's proven mechanism and internal components and incorporates them into a purposeful and attractive torque wrench

In developing NorTorque<sup>®</sup>, Norbar's objective was to deliver outstanding quality and performance in a value for money package. Fine engineering ensures that the wrench adjustment is both fast and fingertip light meaning that you can do your job more efficiently.

Supplied with a Declaration of Conformance which meets the requirements ISO 6789-1:2017

Accurate to  $\pm 3\%$  of reading with models available to cover 12 N·m to 300 N·m.

**Part number:** 130104

**EAN Bar Code:** 5060207565363

**NATO number:** 5120-99-1636457

**Accuracy:**  $\pm 3\%$

**Operates between:**

**40.00 - 200.00 N·m**

**30.00 - 150.00 lbf·ft**



## TECHNICAL SPECIFICATIONS

- Length: 459mm
- Weight: 1kg
- Ratchet Teeth: 72
- Square Drive: 1/2"
- Ratchet Diameter: 45mm
- Scale Increments (N·m): 1
- Scale Increments (lbf·ft): 2

## FEATURES

- Push through ratchets with a narrow engagement angle of 5° for working in tight spaces
- Convenient hanger feature for tool storage also aids wrench unlocking and adjustment
- Just eight turns to cover the entire scale
- Micrometer scale applying to the primary torque units (N·m on a dual scale wrench) for simple and error free setting
- Push/pull lock is fast and intuitive to use and prevents accidental adjustment of the set torque
- Light and fast adjustment saves operator time and effort
- Supplied with a Declaration of Conformance, which meets the requirements of ISO 6789-1:2017

NORBAR TORQUE TOOLS LTD. Wildmere Road, Banbury, Oxfordshire, OX16 3JU,  
United Kingdom  
Registered Office as above - Registered in England No. 380480 - VAT No. GB  
119 1060 05

- Tel: + 44 (0) 1295 270333
- Enquiries: + 44 (0) 1295 753600
- Email: [enquiry@norbar.com](mailto:enquiry@norbar.com)
- After Sales: + 44 (0) 1295 753635
- Email: [service@norbar.com](mailto:service@norbar.com)